

Prosthetic overview PF 3.5

NOTICE:

- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
- In each case, the symbols correspond to required components, which can be ordered separately I - VII.
- Rotation locked Rotation unlocked





Screws	Gingiva former
Applicable for all restorations	Applicable for all restorations
Occlusal screw	Gingiva former customizable
Length 3.5 mm 4.03.507	Height 7.5 mm 4.03.576
Screw for bar	Healing cap SE
Length 4.3 mm 4.03.506	Height 1.0 mm 4.03.515
Abutment screw	Gingiva former
Length 5.8 mm 4.03.508	Height 2.0 mm 4.03.530 3.2 mm 4.03.530 4.5 mm 4.03.540 5.7 mm 4.03.560 7.0 mm 4.03.550
VARIOmulti fabrication screw	Gingiva former narrow
Length Pcs. 19.3 mm 4 3.03.598 04	Height 2.0 mm 4.04.310 3.2 mm 4.04.330 4.5 mm 4.04.330 5.7 mm 4.04.340 7.0 mm 4.04.350
Laboratory screw	
Length 25.0 mm 3.03.515	
Fabrication screw	
Length Pcs. 22.5 mm 4 3.03.590 04	
Dynamic Abutment screw	
Length 6.9 mm 41.314.069.01-2	












	Impression taking	Temp. restoration	Final restoration	Burn-out cap	Analogue		
Cemented	EASY impression coping	EASY temporary cap	EASY abutment Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 4.03.700 short 0.5 mm 6.0 mm 6.5 mm 4.03.704 long 2.0 mm 4.0 mm 6.0 mm 4.03.710 long 2.0 mm 6.0 mm 8.0 mm 4.03.714 extra long 4.0 mm 6.0 mm 10.0 mm 4.03.734	EASY abutment 20° Collar Height 20° short 0.5 mm 6.5 mm 4.03.010 20° long 3.0 mm 8.0 mm 4.03.014	EASY burn-out cap Height Cone 4.7 mm 4.0 mm 2.03.720 6.7 mm 6.0 mm 2.03.724 4.7 mm 4.0 mm 2.03.730* 6.7 mm 6.0 mm 2.03.734*	EASY analog Cone 4.0 mm 3.03.700 6.0 mm 3.03.704	Implant analog Length 22.0 mm 3.03.060 14.0 mm 3.03.090
			EASY abutment set Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 1.04.700 short 0.5 mm 6.0 mm 6.5 mm 1.04.704 long 2.0 mm 4.0 mm 6.0 mm 1.04.710 long 2.0 mm 6.0 mm 8.0 mm 1.04.714 extra long 4.0 mm 6.0 mm 10.0 mm 1.04.734			Implant analog for CAD/CAM Length 11.4 mm 3.03.085	
			Set contents: - EASY abutment - abutment screw - EASY impression coping - EASY analog - EASY temporary cap - EASY burn-out cap, for crown, burn-out plastic - EASY burn-out cap, for bridge, burn-out plastic				
Screw-retained & cemented	Impression copings Closed tray Open tray Screws Titanium Conical Conical Parallel 3.04.030 3.04.046 3.04.020 Alu Conical Conical Parallel 3.03.074 3.03.014 3.03.010	VARIOtemp set Fabrication screw included Height 12.0 mm 1.04.080 12.0 mm 1.04.085*	ART abutment set ZrO ₂ Abutment screw included Cone Height 6.0 mm 9.0 mm 1.03.623	ART grinding cylinder set ZrO ₂ Abutment screw included Height 12.0 mm 1.03.649	Dynamic Tibase® Abutment screw included Height 4.0 mm 31.311.113.01-2 4.0 mm 31.321.113.01-2*	Dynamic Tibase® customizable length Abutment screw included Height 9.0 mm 31.310.113.21-2 9.0 mm 31.320.113.21-2*	
	Scan abutment Stainless steel, coated 3.03.775	Screw for impression coping Length 12.3 mm 3.03.572		VARIOflex set Abutment screw, burn-out cap included Height 12.0 mm 1.04.830 12.0 mm 1.04.835*	Titanium Base CAD/CAM set Abutment screw included Height 5.2 mm 1.04.750 5.2 mm 1.04.760*	Milling abutment for CAD/CAM Type II Abutment screw included Length Ø 13.0 mm 8.0 mm 1.04.401	
				VARIOeco burn-out cap Height 12.0 mm 2.03.790	VARIOflex burn-out cap Height 11.5 mm 2.03.840	Implant analog for CAD/CAM Length 11.4 mm 3.03.085	
Screw-retained	Impression copings Closed tray Open tray Screws Titanium Conical Conical Parallel 3.04.030 3.04.046 3.04.020 Alu Conical Conical Parallel 3.03.074 3.03.014 3.03.010	VARIOtemp set Fabrication screw included Height 12.0 mm 1.04.080 12.0 mm 1.04.085*	VARIO abutment 17° set 0° Height Shoulder height Type A 5.6 mm 0.5 mm 1.03.160 30° Height Shoulder height Type B 5.6 mm 0.5 mm 1.03.180	VARIO gold abutment, NOA Height Cone 12.7 mm 3.5 mm 2.03.410 12.7 mm 3.5 mm 2.03.400*	VARIO 17° gold screw seat Height 11.3 mm 2.9 mm 2.03.610	Implant analog for CAD/CAM Length 11.4 mm 3.03.085	
						Implant analog Length 22.0 mm 3.03.060 14.0 mm 3.03.090	
	VARIOmulti impression coping Open tray Screws VARIOmulti Height 18.0 mm 3.04.805	VARIOmulti protective cap Height 4.5 mm 4.03.801	VARIOmulti temp. cap Fabrication screw included Height 15.0 mm 3.03.804	VARIOmulti straight Height Shoulder height 3.0 mm 0.8 mm 4.03.600 4.2 mm 2.0 mm 4.03.605 5.2 mm 3.0 mm 4.03.610	VARIOmulti angled Angle Height Shoulder height 17° 4.3 mm 2.9 mm 4.03.680 30° 4.4 mm 3.3 mm 4.03.685	VARIOmulti gold cap NOA Height Ø 4.2/13.5 mm 4.8 mm 2.03.600	VARIOmulti burn-out cap Height Ø pcs. 13.5 mm 4.8 mm 2 2.03.601 02
						VARIOmulti analog Height Ø 21.2 mm 4.8 mm 3.03.800	
	VARIOmulti Scan abutment Height Ø 8.0 mm 4.5 mm 3.03.780	VARIOmulti Scan abutment, short Height Ø 5.0 mm 5.0 mm 3.03.781		VARIOmulti titanium base for CAD/CAM incl. occlusal screw Height Ø 4.5 mm 4.8 mm 1.04.850	VARIOmulti titanium base for CAD/CAM, customizable length incl. occlusal screw Height Ø 9.0 mm 4.8 mm 1.04.851	VARIOmulti analog for CAD/CAM Height Ø 13.2 mm 4.8 mm 3.03.083	
Overdenture	LOCATOR® abutment impression coping Alu 4 pcs. 8505	Bar abutment impression coping Height Ø 5.0 mm 6.0 mm 3.03.101	LOCATOR® male processing 20 pcs. 8515-20	LOCATOR® abutment Height 0.73 mm 8875 2.0 mm 8876 3.0 mm 8877 4.0 mm 8878 5.0 mm 8879* 6.0 mm 8880*	RETAIN Milling abutment Height 11.0 mm 4.03.420	LOCATOR® analog Length 21.5 mm 3.03.105 Ø 4.0 mm	
				Bar abutment Height 5.5 mm 4.03.380	Coping for bar Gold 2.03.335 Titanium 4.03.070	LOCATOR® analog Height Ø Pcs. 4.0 mm 4 8530 5.0 mm 4 8516	
					LOCATOR® For components, see: thommenmedical.com or product catalogue		
























































*Only available in the US.

Prosthetic overview PF 4.0

NOTICE:

- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
- In each case, the symbols correspond to required components, which can be ordered separately  .
- Rotation locked  Rotation unlocked 

Screws	Gingiva former
<p>Applicable for all restorations</p>	<p>Applicable for all restorations</p>
<p>Occlusal screw</p>  <p>Length 3.5 mm 4.03.507</p>	<p>Gingiva former customizable</p>  <p>Height 7.5 mm 4.03.571</p>
<p>Screw for bar</p>  <p>Length 4.3 mm 4.03.506</p>	<p>Healing cap SE</p>  <p>Height 1.6 mm 4.03.519</p>
<p>Abutment screw</p>  <p>Length 7.2 mm 4.03.501 10.2 mm 4.03.502</p>	<p>Gingiva former</p>  <p>Height 2.0 mm 4.03.522 3.2 mm 4.03.534 4.5 mm 4.03.544 5.7 mm 4.03.544 7.0 mm 4.03.554</p>
<p>VARIOMulti fabrication screw</p>  <p>Length 19.3 mm 4 3.03.598.04</p>	<p>Gingiva former narrow</p>  <p>Height 2.0 mm 4.04.311 3.2 mm 4.04.321 4.5 mm 4.04.331 5.7 mm 4.04.341 7.0 mm 4.04.351</p>
<p>Laboratory screw</p>  <p>Length 25.0 mm 3.03.516</p>	
<p>Fabrication screw</p>  <p>Length 23.4 mm 4 3.03.591.04</p>	
<p>Dynamic abutment screw</p>  <p>Length 6.9 mm 41.316.076.02-2</p>	












	Impression taking	Temp. restoration	Final restoration	Burn-out cap	Analog	
Cemented	<p>EASY impression coping</p>  <p>Height Cone EASY 9.5 mm 4.0 mm 2.03.708 EASY 11.5 mm 6.0 mm 2.03.709 EASY e.p. 9.5 mm 4.0 mm 2.03.701 EASY e.p./ART 11.5 mm 6.0 mm 2.03.705</p>	<p>EASY temporary cap</p>  <p>Height Cone EASY 5.0 mm 4.0 mm 2.03.748 EASY 7.0 mm 6.0 mm 2.03.749 EASY e.p. 5.0 mm 4.0 mm 2.03.741 EASY e.p./ART 7.0 mm 6.0 mm 2.03.745</p>	<p>EASY abutment</p>  <p>Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 4.03.708 short 0.5 mm 6.0 mm 6.5 mm 4.03.709 long 2.0 mm 4.0 mm 6.0 mm 4.03.718 long 2.0 mm 6.0 mm 8.0 mm 4.03.719 extra long 4.0 mm 6.0 mm 10.0 mm 4.03.739</p> <p>EASY abutment set</p>  <p>Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 1.04.708 short 0.5 mm 6.0 mm 6.5 mm 1.04.709 long 2.0 mm 4.0 mm 6.0 mm 1.04.718 long 2.0 mm 6.0 mm 8.0 mm 1.04.719 extra long 4.0 mm 6.0 mm 10.0 mm 1.04.739</p> <p>Set contents: - EASY abutment - abutment screw - EASY impression coping - EASY analog - EASY temporary cap - EASY burn-out cap for crown - EASY burn-out cap for bridge</p> <p>EASY abutment e.p.</p>  <p>Height Cone 7.0 mm 4.0 mm 4.03.728 9.0 mm 6.0 mm 4.03.729</p>	<p>EASY burn-out cap</p>  <p>Height Cone EASY 4.7 mm 4.0 mm 2.03.728 EASY 6.7 mm 6.0 mm 2.03.729 EASY 4.7 mm 4.0 mm 2.03.738* EASY e.p. 4.7 mm 4.0 mm 2.03.739* EASY e.p. 6.7 mm 4.0 mm 2.03.725 EASY e.p. 4.7 mm 4.0 mm 2.03.731* EASY e.p. 6.7 mm 4.0 mm 2.03.735*</p>	<p>EASY analog</p>  <p>Cone EASY 4.0 mm 3.03.706 EASY 6.0 mm 3.03.709 EASY e.p. 4.0 mm 3.03.701 EASY e.p. 6.0 mm 3.03.705</p>	<p>Implant analog</p>  <p>Length 22.0 mm 3.03.061 14.0 mm 3.03.095</p> <p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.086</p>
Screw-retained & cemented	<p>Impression copings</p>  <p>Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.031 3.04.047 3.03.078 3.04.037 Alu Conical Conical Parallel Parallel 3.03.079 3.03.019 3.03.018 3.04.021</p> <p>Scan abutment Screw for impression coping Stainless steel, coated 3.03.776 Length 13.2 mm 3.03.575</p>	<p>VARIOTemp set</p>  <p>Fabrication screw included Height 12.0 mm 1.04.681 12.0 mm 1.04.086*</p>	<p>ART abutment set</p>  <p>Abutment screw included Cone Height 6.0 mm 9.0 mm 1.03.624</p> <p>ART grinding cylinder set</p>  <p>Abutment screw included Height 12.0 mm 1.03.650</p> <p>Dynamic Tibase®</p>  <p>Abutment screw included Height 4.0 mm 31.312.114.01-2 4.0 mm 31.322.114.01-2*</p> <p>Dynamic Tibase® customizable length</p>  <p>Abutment screw included Height 9.0 mm 31.312.114.21-2 9.0 mm 31.322.114.21-2*</p>	<p>EASY burn-out cap</p>  <p>ART Height Cone ART 6.7 mm 6.0 mm 2.03.725 ART 6.7 mm 6.0 mm 2.03.735*</p>	<p>EASY analog</p>  <p>Cone ART 6.0 mm 3.03.705</p>	<p>Implant analog</p>  <p>Length 22.0 mm 3.03.061 14.0 mm 3.03.095</p>
Screw-retained	<p>Impression copings</p>  <p>Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.031 3.04.047 3.03.078 3.04.037 Alu Conical Conical Parallel Parallel 3.03.079 3.03.019 3.03.018 3.04.021</p> <p>Scan abutment Screw for impression coping Stainless steel, coated 3.03.776 Length 13.2 mm 3.03.575</p>	<p>VARIOTemp set</p>  <p>Fabrication screw included Height 12.0 mm 1.04.681 12.0 mm 1.04.086*</p>	<p>VARIOflex set</p>  <p>Abutment screw, burn-out cap included Height 12.0 mm 1.04.831 12.0 mm 1.04.836*</p> <p>Titanium Base CAD/CAM Set</p>  <p>Abutment screw included Height 5.2 mm 1.04.751 5.2 mm 1.04.761*</p> <p>Milling abutment for CAD/CAM Type II</p>  <p>Abutment screw included Length 15.0 mm 11.5 mm 1.04.403</p>	<p>VARIOflex burn-out cap</p>  <p>Height 12.0 mm 2.03.791</p>	<p>VARIOflex burn-out cap</p>  <p>Height 11.5 mm 2.03.841</p>	<p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.086</p>
Screw-retained	<p>Impression copings</p>  <p>Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.031 3.04.047 3.03.078 3.04.037 Alu Conical Conical Parallel Parallel 3.03.079 3.03.019 3.03.018 3.04.021</p> <p>VARIOMulti impression coping Open tray Screws Height 18.0 mm 3.04.805 3.03.972 3.03.973 3.03.974 3.03.980</p>	<p>VARIOTemp set</p>  <p>Fabrication screw included Height 12.0 mm 1.04.681 12.0 mm 1.04.086*</p>	<p>VARIOflex set</p>  <p>Abutment screw, burn-out cap included Height 12.0 mm 1.04.831 12.0 mm 1.04.836*</p> <p>Titanium Base CAD/CAM Set</p>  <p>Abutment screw included Height 5.2 mm 1.04.751 5.2 mm 1.04.761*</p> <p>Milling abutment for CAD/CAM Type II</p>  <p>Abutment screw included Length 15.0 mm 11.5 mm 1.04.403</p>	<p>VARIOflex burn-out cap</p>  <p>Height 12.0 mm 2.03.791</p>	<p>VARIOflex burn-out cap</p>  <p>Height 11.5 mm 2.03.841</p>	<p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.086</p>
Screw-retained	<p>VARIOMulti impression coping</p>  <p>Open tray Screws Height 18.0 mm 3.04.805 3.03.972 3.03.973 3.03.974 3.03.980</p> <p>VARIOMulti Scan abutment</p>  <p>Height 8.0 mm 4.5 mm 3.03.780</p> <p>VARIOMulti Scan abutment, short</p>  <p>Height 5.0 mm 6.0 mm 3.03.781</p>	<p>VARIOMulti protective cap</p>  <p>Height 4.5 mm 4.03.801</p> <p>VARIOMulti temp. cap</p>  <p>Fabrication screw included Height 15.0 mm 3.03.804</p>	<p>VARIOflex set</p>  <p>Abutment screw, burn-out cap included Height 12.0 mm 1.04.831 12.0 mm 1.04.836*</p> <p>Titanium Base CAD/CAM Set</p>  <p>Abutment screw included Height 5.2 mm 1.04.751 5.2 mm 1.04.761*</p> <p>Milling abutment for CAD/CAM Type II</p>  <p>Abutment screw included Length 15.0 mm 11.5 mm 1.04.403</p>	<p>VARIOflex burn-out cap</p>  <p>Height 12.0 mm 2.03.791</p>	<p>VARIOflex burn-out cap</p>  <p>Height 11.5 mm 2.03.841</p>	<p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.086</p>
Overdenture	<p>LOCATOR® Abutment impression coping</p>  <p>Alu 4 pcs. 8505</p> <p>Bar abutment Impression coping</p>  <p>Height 5.0 mm 6.0 mm 3.03.101</p>	<p>LOCATOR® male processing</p>  <p>20 pcs. 8515-20</p>	<p>LOCATOR® abutment</p>  <p>Height 1.0 mm 8461 2.0 mm 8462 3.0 mm 8463 4.0 mm 8464 5.0 mm 8465 6.0 mm 8466</p> <p>Retentive anchor abutment</p>  <p>Height 1.8 mm 4.03.048 3.0 mm 4.03.049</p>	<p>RETAIN Milling abutment</p>  <p>Height 12.0 mm 4.03.428</p> <p>Bar abutment</p>  <p>Height 5.5 mm 4.03.388</p> <p>Coping for bar</p>  <p>Gold 2.03.335 Titanium 4.03.070</p>	<p>LOCATOR® analog</p>  <p>Length 13.0 mm 3.03.033</p>	<p>Retentive anchor analog</p>  <p>Length 4.0 mm 4 8530 5.0 mm 4 8516</p>


















































LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Prosthetic overview PF 4.5

NOTICE:

- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
- In each case, the symbols correspond to required components, which can be ordered separately I - VII.
- Rotation locked Rotation unlocked




Screws	Gingiva former
<p>Applicable for all restorations</p>	<p>Applicable for all restorations</p>
<p>Occlusal screw</p>  <p>Length 3.5 mm 4.03.507</p>	<p>Gingiva former customizable</p>  <p>Height 7.5 mm 4.03.572</p>
<p>Screw for bar</p>  <p>Length 4.3 mm 4.03.506</p>	<p>Healing cap SE</p>  <p>Height 1.0 mm 4.03.516</p>
<p>Abutment screw</p>  <p>Length 7.2 mm 4.03.501 10.2 mm 4.03.502</p>	<p>Gingiva former</p>  <p>Height 2.0 mm 4.03.521 3.2 mm 4.03.531 4.5 mm 4.03.541 5.7 mm 4.03.541 7.0 mm 4.03.551</p>
<p>VARIOMulti fabrication screw</p>  <p>Length Pcs 19.3 mm 4 3.03.598.04</p>	<p>Gingiva former narrow</p>  <p>Height 2.0 mm 4.04.312 3.2 mm 4.04.322 4.5 mm 4.04.332 5.7 mm 4.04.342 7.0 mm 4.04.352</p>
<p>Laboratory screw</p>  <p>Length 25.0 mm 4 3.03.516</p>	
<p>Fabrication screw</p>  <p>Length Pcs 23.4 mm 4 3.03.591.04</p>	
<p>Dynamic Abutment screw</p>  <p>Length 6.9 mm 41.316.076.02-2</p>	












	Impression taking	Temp. restoration	Final restoration	Burn-out cap	Analogue
Cemented	<p>EASY impression coping</p>  <p>Height Cone EASY 9.5 mm 4.0 mm 2.03.701 EASY 11.5 mm 6.0 mm 2.03.705 EASY e.p. 9.5 mm 4.0 mm 2.03.702 EASY e.p./ART 11.5 mm 6.0 mm 2.03.706</p>	<p>EASY temporary cap</p>  <p>Height Cone EASY 5.0 mm 4.0 mm 2.03.741 EASY 7.0 mm 6.0 mm 2.03.745 EASY e.p. 5.0 mm 4.0 mm 2.03.742 EASY e.p./ART 7.0 mm 6.0 mm 2.03.746</p>	<p>EASY abutment</p>  <p>Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 4.03.701 short 0.5 mm 6.0 mm 6.5 mm 4.03.705 long 2.0 mm 4.0 mm 6.0 mm 4.03.711 long 2.0 mm 6.0 mm 8.0 mm 4.03.715 extra long 4.0 mm 6.0 mm 10.0 mm 4.03.735</p> <p>EASY abutment set</p>  <p>Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 1.04.701 short 0.5 mm 6.0 mm 6.5 mm 1.04.705 long 2.0 mm 4.0 mm 6.0 mm 1.04.711 long 2.0 mm 6.0 mm 8.0 mm 1.04.715 extra long 4.0 mm 6.0 mm 10.0 mm 1.04.735</p> <p>Set contents: EASY abutment abutment screw EASY impression coping EASY analogue EASY temporary cap EASY burn-out cap for crown EASY burn-out cap for bridge</p> <p>EASY abutment e.p.</p>  <p>Height Cone 7.0 mm 4.0 mm 4.03.721 9.0 mm 6.0 mm 4.03.725</p>	<p>EASY burn-out cap</p>  <p>Height Cone EASY 4.7 mm 4.0 mm 2.03.721 EASY 6.7 mm 6.0 mm 2.03.725 EASY 4.7 mm 4.0 mm 2.03.731* EASY e.p. 4.7 mm 4.0 mm 2.03.722 EASY e.p. 6.7 mm 6.0 mm 2.03.726 EASY e.p. 4.7 mm 4.0 mm 2.03.732* EASY e.p. 6.7 mm 6.0 mm 2.03.736*</p>	<p>EASY analog</p>  <p>Cone EASY 4.0 mm 3.03.701 EASY 6.0 mm 3.03.705 EASY e.p. 4.0 mm 3.03.702 EASY e.p. 6.0 mm 3.03.706</p> <p>Implant analog</p>  <p>Length 22.0 mm 3.03.065 14.0 mm 3.03.091</p> <p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.087</p>
Screw-retained & cemented	<p>Impression copings</p>  <p>Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.032 3.04.048 3.03.071 3.04.038 Alu Titanium 3.03.575 3.03.576 3.03.577 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm</p> <p>Scan abutment</p>  <p>Stainless steel, coated 3.03.777</p> <p>Screw for impression coping</p>  <p>Length 3.03.575</p>	<p>VARIOTemp set</p>  <p>Fabrication screw included Height 12.0 mm 1.04.682 12.0 mm 1.04.087*</p>	<p>ART abutment set</p>  <p>ZrO₂ Abutment screw included Cone Height 6.0 mm 9.0 mm 1.03.625</p> <p>ART grinding cylinder set</p>  <p>ZrO₂ Abutment screw included Height 12.0 mm 1.03.651</p> <p>Dynamic Tibase®</p>  <p>Abutment screw included Height 4.0 mm 31.313.115.01-2 4.0 mm 31.323.115.01-2*</p> <p>Dynamic Tibase® customizable length</p>  <p>Abutment screw included Height 9.0 mm 31.313.115.21-2 9.0 mm 31.323.115.21-2*</p>	<p>EASY burn-out cap</p>  <p>Height Cone ART 6.7 mm 6.0 mm 2.03.726 ART 6.7 mm 6.0 mm 2.03.736*</p>	<p>EASY analog</p>  <p>Cone ART 6.0 mm 3.03.706</p> <p>Implant analog</p>  <p>Length 22.0 mm 3.03.065 14.0 mm 3.03.091</p> <p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.087</p>
Screw-retained	<p>Impression copings</p>  <p>Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.032 3.04.048 3.03.071 3.04.038 Alu Titanium 3.03.575 3.03.576 3.03.577 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm</p> <p>VARIOMulti impression coping</p>  <p>Open tray Screws Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 12.5 mm 16.5 mm 21.5 mm 27.5 mm</p> <p>VARIOMulti Scan abutment</p>  <p>Height Ø 8.0 mm 4.5 mm 3.03.780</p> <p>VARIOMulti Scan abutment, short</p>  <p>Height Ø 5.0 mm 5.0 mm 3.03.781</p>	<p>VARIOTemp set</p>  <p>Fabrication screw included Height 12.0 mm 1.04.682 12.0 mm 1.04.087*</p>	<p>VARIO abutment 17° set</p>  <p>Set contents: VARIO abutment 17° (titanium) VARIO 17° gold screw seat occlusal screw abutment screw</p> <p>0° Height Shoulder height Type A 5.6 mm 0.5 mm 1.03.162</p> <p>30° Height Shoulder height Type B 5.4 mm 0.5 mm 1.03.182</p> <p>VARIO gold abutment, NOA</p>  <p>Height Cone 12.7 mm 3.5 mm 2.03.411 12.7 mm 3.5 mm 2.03.401*</p>	<p>VARIO 17° gold screw seat</p>  <p>Height Ø 11.3 mm 2.9 mm 2.03.610</p>	<p>Implant analog for CAD/CAM</p>  <p>Length 11.4 mm 3.03.087</p> <p>Implant analog</p>  <p>Length 22.0 mm 3.03.065 14.0 mm 3.03.091</p>
Overdenture	<p>VARIOMulti protective cap</p>  <p>Height 4.5 mm 4.03.801</p> <p>VARIOMulti temp. cap</p>  <p>Fabrication screw included Height 15.0 mm 3.03.804</p>	<p>LOCATOR® male processing</p>  <p>20 pcs. 8515-20</p>	<p>VARIOMulti straight</p>  <p>Height Shoulder height 3.0 mm 0.8 mm 4.03.602 4.2 mm 2.0 mm 4.03.607 5.2 mm 3.0 mm 4.03.612</p> <p>VARIOMulti angled</p>  <p>Angle Height Shoulder height 15° 4.3 mm 2.9 mm 4.03.682 30° 4.4 mm 3.3 mm 4.03.687</p> <p>VARIOMulti gold abutment, NOA</p>  <p>Height Ø 4.2/13.5 mm 4.8 mm 2.03.600</p>	<p>VARIOMulti burn-out cap</p>  <p>Height Ø pcs. 13.5 mm 4.8 mm 2 2.03.601.02</p>	<p>VARIOMulti analog</p>  <p>Height Ø 21.2 mm 4.8 mm 3.03.800</p> <p>VARIOMulti analog for CAD/CAM</p>  <p>Height Ø 13.2 mm 4.8 mm 3.03.083</p>
	<p>LOCATOR® Abutment impression coping</p>  <p>Alu 4 pcs. 8505</p> <p>Bar abutment Impression coping</p>  <p>Height Ø 5.0 mm 6.0 mm 3.03.101</p>		<p>LOCATOR® abutment</p>  <p>Height 1.0 mm 8786 2.0 mm 8787 3.0 mm 8788 4.0 mm 8789 5.0 mm 8790 6.0 mm 8791</p> <p>Retentive anchor abutment</p>  <p>Height 1.5 mm 4.03.040 3.0 mm 4.03.041</p>	<p>RETAIN Milling abutment</p>  <p>Height 12.0 mm 4.03.421</p> <p>Bar abutment</p>  <p>Height 5.5 mm 4.03.381</p> <p>Coping for bar</p>  <p>Gold 2.03.335 Titanium 4.03.070</p>	<p>Retentive anchor analog</p>  <p>Length 13.0 mm 3.03.033</p> <p>LOCATOR® analog</p>  <p>Height Pcs 4.0 mm 4 8530 5.0 mm 4 8516</p>










































LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Prosthetic overview PF 5.0

NOTICE:

- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
- In each case, the symbols correspond to required components, which can be ordered separately  - .
- Rotation locked  Rotation unlocked 

Screws	Gingiva former
	Applicable for all restorations
Occlusal screw	Gingiva former customizable
 Length 3.5 mm 4.03.507	 Height 7.5 mm 4.03.573
Screw for bar	Healing cap SE
 Length 4.3 mm 4.03.506	 Height 1.0 mm 4.03.517
Abutment screw	Gingiva former
 Length 7.2 mm 4.03.501 10.2 mm 4.03.502	 Height 4.03.522 3.2 mm 4.03.522 4.5 mm 4.03.542 5.7 mm 4.03.562 7.0 mm 4.03.552
VARIOmulti fabrication screw	Gingiva former narrow
 Length 19.3 mm 4 3.03.596 04	 Height 4.04.313 2.0 mm 4.04.313 3.2 mm 4.04.323 4.5 mm 4.04.333 5.7 mm 4.04.343 7.0 mm 4.04.353
Laboratory screw	
 Length 25.0 mm 3.03.516	
Fabrication screw	
 Length 23.4 mm Pcs 3.03.591 04	
Dynamic Abutment screw	
 Length 8.9 mm 4.1316.076.02-2	

	Impression taking	Temp. restoration	Final restoration		Burn-out cap	Analog			
Cemented	EASY impression coping	EASY temporary cap	EASY abutment	EASY abutment 20°	EASY burn-out cap	EASY analog	Implant analog		
	 Height Cone EASY 9.5 mm 4.0 mm 2.03.702 EASY 11.5 mm 6.0 mm 2.03.704 EASY e.p. 9.5 mm 4.0 mm 2.03.703 EASY e.p./ART 11.5 mm 6.0 mm 2.03.707	 Height Cone EASY 5.0 mm 4.0 mm 2.03.742 EASY 7.0 mm 6.0 mm 2.03.744 EASY e.p. 5.0 mm 4.0 mm 2.03.743 EASY e.p./ART 7.0 mm 6.0 mm 2.03.747	 Collar Cone Height short 0.5 mm 4.0 mm 4.5 mm 4.03.702 short 0.5 mm 6.0 mm 6.5 mm 4.03.706 long 2.0 mm 4.0 mm 6.0 mm 4.03.712 long 2.0 mm 6.0 mm 8.0 mm 4.03.716 extra long 4.0 mm 6.0 mm 10.0 mm 4.03.736	 Collar Height 20° short 0.5 mm 6.5 mm 4.03.011 20° long 3.0 mm 9.0 mm 4.03.015	 Height Cone EASY 4.7 mm 4.0 mm 2.03.722 EASY 6.7 mm 6.0 mm 2.03.724 EASY 4.7 mm 4.0 mm 2.03.732* EASY e.p. 4.7 mm 4.0 mm 2.03.723 EASY e.p. 6.7 mm 6.0 mm 2.03.727* EASY e.p. 4.7 mm 4.0 mm 2.03.733* EASY e.p. 6.7 mm 6.0 mm 2.03.737*	 Cone EASY 4.0 mm 3.03.702 EASY 6.0 mm 3.03.704 EASY e.p. 4.0 mm 3.03.703 EASY e.p. 6.0 mm 3.03.707	 Length 22.0 mm 3.03.065 14.0 mm 3.03.092	Implant analog for CAD/CAM	
Screw-retained & cemented	Impression copings	VARIOtemp set	ART abutment set	ART grinding cylinder set	Dynamic Tibase®	Dynamic Tibase® customizable length	EASY burn-out cap	EASY analog	Implant analog
	 Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.033 3.04.049 3.03.072 3.04.039 Alu Titanium 3.03.575 3.03.576 3.03.577 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm	 Fabrication screw included Height 12.0 mm 1.04.083 12.0 mm 1.04.088*	 Abutment screw included Cone Height 6.0 mm 9.0 mm 1.03.626	 Abutment screw included Height 12.0 mm 1.03.652	 Abutment screw included Height 4.0 mm 3.1314.116.01-2 4.0 mm 3.1324.116.01-2*	 Abutment screw included Height 9.0 mm 3.1314.116.21-2 9.0 mm 3.1324.116.21-2*	 Height Cone ART 6.7 mm 6.0 mm 2.03.727 ART 6.7 mm 6.0 mm 2.03.737*	 Cone ART 6.0 mm 3.03.707	 Length 22.0 mm 3.03.062 14.0 mm 3.03.092
Screw-retained	Scan abutment	Screw for impression coping	VARIOflex set	Titanium Base CAD/CAM Set	Milling abutment for CAD/CAM Type II	VARIOeco burn-out cap	VARIOflex burn-out cap	Implant analog for CAD/CAM	Implant analog for CAD/CAM
	 Stainless steel, coated 3.03.778	 Length 13.2 mm 3.03.575	 Abutment screw, burn-out cap included Height 12.0 mm 1.04.833* 12.0 mm 1.04.838*	 Abutment screw included Height 5.2 mm 1.04.753 5.2 mm 1.04.763*	 Abutment screw included Length 15.0 mm 11.5 mm 1.04.407	 Height 12.0 mm 2.03.793	 Height 11.5 mm 2.03.843	 Length 11.4 mm 3.03.088	 Length 22.0 mm 3.03.062 14.0 mm 3.03.092
Overdenture	Impression copings	VARIOtemp set	VARIO abutment 17° set	VARIO gold abutment, NOA	VARIO 17° gold screw seat	Implant analog for CAD/CAM	Implant analog for CAD/CAM		
	 Closed tray Open tray Screws Titanium Conical Conical Conical Conical 3.04.033 3.04.049 3.03.072 3.04.039 Alu Titanium 3.03.076 3.03.076 3.03.077 3.03.081 13.2 mm 17.2 mm 22.2 mm 28.2 mm	 Fabrication screw included Height 12.0 mm 1.04.083 12.0 mm 1.04.088*	 Set contents: - VARIO abutment 17° (titanium) - VARIO 17° gold screw seat - occlusal screw - abutment screw Height Shoulder height Type A 5.6 mm 0.5 mm 1.03.163 30° Height Shoulder height Type B 5.6 mm 0.5 mm 1.03.183	 Height Cone 12.7 mm 3.5 mm 2.03.412 12.7 mm 3.5 mm 2.03.402*	 Height 11.3 mm 2.9 mm 2.03.610	 Length 11.4 mm 3.03.088	 Length 22.0 mm 3.03.062 14.0 mm 3.03.092		
Overdenture	VARIOmulti impression coping	VARIOmulti protective cap	VARIOmulti straight	VARIOmulti angled	VARIOmulti gold abutment, NOA	VARIOmulti burn-out cap	VARIOmulti analog		
	 Open tray Screws Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 12.5 mm 16.5 mm 21.5 mm 27.5 mm	 Height 4.03.801	 Height Shoulder height 3.0 mm 0.8 mm 4.03.603 4.2 mm 2.0 mm 4.03.608 5.2 mm 3.0 mm 4.03.613	 Angle Height Shoulder height 17° 4.3 mm 2.7 mm 4.03.683 30° 4.4 mm 3.3 mm 4.03.688	 Height 4.2/13.5 mm 4.8 mm 2.03.600	 Height 13.5 mm 4.8 mm 2 2.03.601 02	 Height 21.2 mm 4.8 mm 3.03.800		
Overdenture	VARIOmulti Scan abutment	VARIOmulti Scan abutment, short	VARIOmulti titanium base for CAD/CAM	VARIOmulti titanium base for CAD/CAM, customizable length	VARIOmulti titanium base for CAD/CAM, customizable length	VARIOmulti titanium base for CAD/CAM, customizable length	VARIOmulti titanium base for CAD/CAM, customizable length		
	 Height 8.0 mm 4.5 mm 3.03.780	 Height 5.0 mm 5.0 mm 3.03.781	 incl. occlusal screw Height 4.5 mm 4.3 mm 1.04.850	 incl. occlusal screw Height 9.0 mm 4.8 mm 1.04.851	 incl. occlusal screw Height 9.0 mm 4.8 mm 1.04.851	 Height 13.2 mm 4.8 mm 3.03.083	 Height 13.2 mm 4.8 mm 3.03.083		
Overdenture	LOCATOR® Abutment impression coping	Bar abutment Impression coping	LOCATOR® male processing	LOCATOR® abutment	Retentive anchor® abutment	RETAIN Milling abutment	LOCATOR® For components, see: thommenmedical.com or product catalogue	Retentive anchor analog	LOCATOR® analog
	 Alu 4 pcs. 8505	 Height 5.0 mm 6.0 mm 3.03.101	 20 pcs. 8515-20	 Height 1.0 mm 8792 2.0 mm 8793 3.0 mm 8794 4.0 mm 8795 5.0 mm 8796 6.0 mm 8797	 Height 1.5 mm 4.03.042 3.0 mm 4.03.043	 Height 12.0 mm 4.03.422	 Height 5.5 mm 4.03.382	 For components, see: thommenmedical.com or product catalogue	 Length 13.0 mm 3.03.033

Prosthetic overview PF 6.0

NOTICE: For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
In each case, the symbols correspond to required components, which can be ordered separately - .
Rotation locked Rotation unlocked

Screws	Gingiva former
<p>Occlusal screw</p> <p>Length 3.5 mm 4.03.507</p>	<p>Applicable for all restorations</p> <p>Gingiva former customizable</p> <p>Height 7.5 mm 4.03.574</p>
<p>Screw for bar</p> <p>Length 4.3 mm 4.03.506</p>	<p>Healing cap SE</p> <p>Height 1.0 mm 4.03.518</p>
<p>Abutment screw</p> <p>Length 7.2 mm 4.03.501 10.2 mm 4.03.502</p>	<p>Gingiva former</p> <p>Height 2.0 mm 4.03.523 3.2 mm 4.03.533 4.5 mm 4.03.543 5.7 mm 4.03.543 7.0 mm 4.03.553</p>
<p>VARIOmulti fabrication screw</p> <p>Length Pcs. 19.3 mm 4 3.03.598 04</p>	<p>Gingiva former narrow</p> <p>Height 2.0 mm 4.04.314 2.0 mm 4.04.324 3.2 mm 4.04.334 4.5 mm 4.04.344 5.7 mm 4.04.344 7.0 mm 4.04.354</p>
<p>Laboratory screw</p> <p>Length 25.0 mm 3.03.516</p>	
<p>Fabrication screw</p> <p>Length Pcs. 23.4 mm 4 3.03.591 04</p>	

	Impression taking	Temp. restoration	Final restoration	Burn-out cap	Analog			
Cemented	<p>EASY impression coping</p> <p>Height Cone 2.03.703 9.5 mm 4.0 mm 2.03.707 11.5 mm 6.0 mm</p>	<p>EASY temporary cap</p> <p>Height Cone 2.03.743 5.0 mm 4.0 mm 2.03.747 7.0 mm 6.0 mm</p>	<p>EASY abutment</p> <p>Collar Cone Height 4.03.703 short 0.5 mm 4.0 mm 4.5 mm 4.03.707 long 2.0 mm 6.0 mm 6.0 mm 4.03.713 long 2.0 mm 6.0 mm 8.0 mm 4.03.717</p> <p>EASY abutment 20°</p> <p>Collar Height 4.03.011 20° short 0.5 mm 6.5 mm 4.03.015 20° long 3.0 mm 9.0 mm</p> <p>EASY abutment set</p> <p>Set contents: - EASY abutment - abutment screw - EASY impression coping - EASY analog - EASY temporary cap - EASY burn-out cap, for crown, burn-out plastic - EASY burn-out cap, for bridge, burn-out plastic</p> <p>Collar Cone Height 1.04.703 short 0.5 mm 4.3 mm 4.5 mm 1.04.707 short 0.5 mm 6.0 mm 6.5 mm 1.04.713 long 2.0 mm 6.0 mm 6.0 mm 1.04.713 long 2.0 mm 6.0 mm 8.0 mm 1.04.717</p>	<p>EASY burn-out cap</p> <p>Height Cone 2.03.723 4.7 mm 4.0 mm 2.03.727 4.7 mm 4.0 mm 2.03.733* 6.7 mm 6.0 mm 2.03.737*</p>	<p>EASY analog</p> <p>Cone 3.03.703 4.0 mm 3.03.707 6.0 mm</p>	<p>Implant analog</p> <p>Length 22.0 mm 3.03.063 15.0 mm 3.03.093</p> <p>Implant analog for CAD/CAM</p> <p>Length 11.4 mm 3.03.089</p>		
Screw-retained & cemented	<p>Impression copings</p> <p>Closed tray Open tray Screws</p> <p>Titanium Conical Conical Conical Conical 3.04.034 3.04.050 3.03.073 3.04.040 Alu Conical Conical Parallel Parallel 3.03.077 3.03.017 3.03.013 3.04.024</p> <p>Scan abutment 3.03.575 Screw for impression coping 3.03.575</p>	<p>VARIOtemp set</p> <p>Fabrication screw included Height 12.0 mm 1.04.684 12.0 mm 1.04.089*</p>	<p>VARIOflex set</p> <p>Abutment screw, burn-out cap included Height 12.0 mm 1.04.834 12.0 mm 1.04.839*</p> <p>Titanium Base CAD/CAM Set</p> <p>Abutment screw included Height 5.2 mm 1.04.754 5.2 mm 1.04.764*</p> <p>Milling abutment for CAD/CAM Type II</p> <p>Abutment screw included Length 13.0 mm 11.5 mm 1.04.409</p>	<p>VARIOeco burn-out cap</p> <p>Height 12.0 mm 2.03.794</p>	<p>VARIOflex burn-out cap</p> <p>Height 11.5 mm 2.03.844</p>	<p>Implant analog</p> <p>Length 22.0 mm 3.03.063 15.0 mm 3.03.093</p> <p>Implant analog for CAD/CAM</p> <p>Length 11.4 mm 3.03.089</p>		
Screw-retained	<p>Impression copings</p> <p>Closed tray Open tray Screws</p> <p>Titanium Conical Conical Conical Conical 3.04.034 3.04.050 3.03.073 3.04.040 Alu Conical Conical Parallel Parallel 3.03.077 3.03.017 3.03.013 3.04.024</p> <p>Scan abutment 3.03.575 Screw for impression coping 3.03.575</p>	<p>VARIOtemp set</p> <p>Fabrication screw included Height 12.0 mm 1.04.684 12.0 mm 1.04.089*</p>	<p>VARIO gold abutment, NOA</p> <p>Height Cone 2.03.413 12.7 mm 3.5 mm 2.03.403* 12.7 mm 3.5 mm</p>	<p>VARIOmulti impression coping</p> <p>Open tray Screws</p> <p>Height 18.0 mm 3.04.805 3.04.972 3.03.973 3.04.974 3.03.980 12.5 mm 16.5 mm 17.2 mm 21.5 mm 27.5 mm</p>	<p>VARIOmulti protective cap</p> <p>Height 4.5 mm 4.03.801</p> <p>VARIOmulti temp. cap</p> <p>Fabrication screw included Height 15.0 mm 3.03.804</p>	<p>VARIOmulti straight</p> <p>Height Shoulder height 4.03.604 3.7 mm 1.5 mm</p> <p>VARIOmulti angled</p> <p>Angle Height Shoulder height 4.03.684 17° 4.3 mm 2.7 mm 4.03.689 30° 4.4 mm 3.3 mm</p> <p>VARIOmulti gold abutment, NOA</p> <p>Height 4.2/13.5 mm 4.8 mm 2.03.600</p>	<p>VARIOmulti burn-out cap</p> <p>Height pcs. 13.5 mm 4.8 mm 2 2.03.601 02</p>	<p>VARIOmulti analog</p> <p>Height 13.2 mm 4.8 mm 3.03.800</p> <p>VARIOmulti analog for CAD/CAM</p> <p>Height 13.2 mm 4.8 mm 3.03.083</p>
Overdenture	<p>VARIOmulti Scan abutment</p> <p>Height 8.0 mm 4.3 mm 3.03.780</p> <p>VARIOmulti Scan abutment, short</p> <p>Height 5.0 mm 5.0 mm 3.03.781</p> <p>LOCATOR® abutment Impression coping</p> <p>Alu 4 pcs. 8505</p>	<p>LOCATOR®</p> <p>male processing 20 pcs. 8515-20</p> <p>Block-out spacer 20 pcs. 8514</p>	<p>LOCATOR® abutment</p> <p>Height 10 mm 8881 2.0 mm 8882 3.0 mm 8883 4.0 mm 8884</p>	<p>RETAIN milling abutment</p> <p>Height 12.0 mm 4.03.423</p>	<p>LOCATOR®</p> <p>For components, see: thommenmedical.com or product catalogue</p>	<p>LOCATOR® analog</p> <p>Height Pcs. 4.0 mm 4 8530 5.0 mm 4 8514</p>		